

# Product Information

A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.



## Valvoline ATF Type II-D

### Description

Valvoline ATF Type II-D is an automatic transmission fluid designed to meet the service requirements of General Motors Dexron II-D, and is suitable as a service fill for most vehicles.



### Advantages

- Suitable for most passenger car and light truck automatic transmissions.
- Recommended for year round all weather service.
- Suitable for emergency in-service top-up of Ford transmissions requiring ESP-M2-138CJ and M2C-166H type fluids.
- Not recommended for later model transmissions stipulating the use of Dexron II-E or Dexron III fluids.

### Approvals / Performance Levels

G.M. Dexron II-D: Allison C3  
Mercedes Benz 236.3  
ZF TE-ML-11 (Passenger Car): ZF-TE-ML-14 (Commercial Vehicle): ZF-TE-ML-09 (Power Steering)  
VW service fill: Renault service fill: Voith service fill: BMW service fill: Jaguar service fill: Volvo service fill: SAAB service fill

### Properties

Test	Typical Property
Density @ 20°C	0.867
Viscosity @ 40°C cSt	36.0
Viscosity @ 100°C cSt	7.0
Viscosity Index	159
Pour Point °C	-30
Flash Point C.O.C. °C	160
Colour	Red
BKFD Viscosity @ -40°C cp max	50000

This information only applies to products manufactured in the following location(s):

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:	Code:
09/2004	N/A	6/97	WAR	1	

# Valvoline®