

# Product Information

A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.



## Valvoline Automatic Transmission Fluid Dexron III / Mercon

211/02

### Description

**Valvoline Automatic Transmission Fluid Dexron III / Mercon** is a premium automatic transmission fluid specially formulated to meet the needs of today's more compact transmissions, running at higher operating temperatures and with electronic control. Valvoline ATF Dexron III / Mercon is recommended for use in automatic transmissions, where the manufacturers prescribes a GM Dexron IIE, Dexron III, or Ford Mercon fluid.



### Approvals / Performance Levels

GM Dexron III G-34221  
Ford Mercon M-020602  
Allison C-4  
Nissan (all models)  
Caterpillar TO-2

### Properties

Test	Typical Property
Viscosity, mm <sup>2</sup> /s @ 100 °C	7.7
Viscosity, mm <sup>2</sup> /s @ 40 °C	36.0
Viscosity Index	204
Viscosity, mPa.s -25 °C	1250
Sulphated Ash, wt. %	0.10
TAN; mg KOH/g (ASTM D-664)	1.3
TAN; mg KOH/g (ASTM D-2896)	2.2
Pour Point °C	-40
Specific Gravity @ 15/15°C	0.870
Flash Point, C.O.C. °C	185

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:	Code:
12-04-2001			AdG	1	US

# Valvoline®