

Product Information

A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.



Valvoline DuraBlend Motor Oil

002/07

Description

Valvoline DuraBlend Motor Oil is formulated with a combination of synthetic and premium quality base oils and advanced additive technology. This motor oil helps engines maintain peak performance by providing protection under severe conditions. DuraBlend motor oil meets the performance requirements of virtually all motor vehicles and light trucks (vans), including petrol, diesel, and LPG engines.



Advantages

- **Deposit Control:** Reduces formation of sludge and varnish deposits.
- **Volatility:** Lowers oil vaporization and consumption at extreme temperatures.
- **Cold Start Properties:** Easy Oil Flow at low temperatures.
- **Wear Protection:** Improved oil film strength and breakdown resistance.

Approvals / Performance Levels

API SJ/SL/CF	10W-40
ACEA A3-02, B3-98 issue 2	10W-40
Daimler/Chrysler 229.1	10W-40
VW 500.00 / 505.00 (1/97)	10W-40

Properties

Test	Typical Property
Viscosity, mm/s @ 100 °C	14.2
Viscosity, mm/s @ 40 °C	99
Viscosity Index	153
Viscosity, mPa.s -25 °C	<7000
Sulphated Ash, wt. %	1.20
TAN; mg KOH/g (ASTM D-664)	1.5
TBN; mg KOH/g (ASTM D-2896)	9.0
Pour Point °C	-33
Specific Gravity @ 15/15°C	0.873
Flash Point, C.O.C °C	225
Noack Evaporation, wt. %	12.6

This product is exclusive to Diesel-Electric, conditions apply

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:	Code:
28/12/2004	N/A	002/06	AdG	1	

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence, or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.