

Product Information

A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.



Valvoline XLD SAE 20W-50

Description

Valvoline XLD SAE 20W-50 Motor Oil is a universal multigrade crankcase lubricant of superior quality engineered for use in turbo and multivalve engines.



Advantages

- Suitable for turbo and multivalve engine, both petrol and diesel.
- All mineral formulation with superior inhibition against oxidation, corrosion, foaming, providing outstanding anti-wear capability.
- Quite suitable for mixed-fleet operation over a wide range of operating temperatures.
- Oil consumption well controlled due to excellent shear stability.
- Provides both high and low temperature piston deposit control, maintaining a high degree of engine cleanliness resulting from the Detergent/dispersant additive balance.
- S.A.B.S. APPROVED lubricant and is mark bearing.

Approvals / Performance Levels

API services SH/CG4
ACEA E2-96, A2-96, B2-96
S.A.B.S 1516/1517

Properties

Test	Typical Property
SAE	20W-50
Density @ 20°C	0.884
Viscosity @ 40°C cSt	140.0
Viscosity @ 100°C cSt	18
Viscosity @ -15°C cp	9500 MAX
Viscosity Index	137
Sulfated Ash%	1.05
TBN	9
Pour Point °C	-21
Flash Point C.O.C. °C	215

This information only applies to products manufactured in the following location(s): South Africa

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:	Code:
09/2004	N/A	12/99	WAR	1	

Valvoline®