

# Product Information

A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.



## Valvoline Concrete Mould Release Fluid

### Description

**Valvoline Concrete Mould Release Fluid** is a low viscosity, highly refined mould release oil containing specialised additives that provide a unique release action producing clean, stain free castings. The low viscosity provides maximum coverage.



### Advantages

- Provides a quality, stain-free and smooth surface release that is free of air holes.
- Softens existing build-up on moulds and shuttering.
- Suitable for pre-stressed, pre-cast operations.
- Highly suited to steam curing operations.
- Superior release properties provide reduced quality reject rates.
- Eliminates the need for on-site blending of diesel based "slush oils".
- No offensive odours, improving worker safety and productivity.

### Properties

#### Test

Density @ 20°C  
Kinetic Viscosity @ 40 °C cSt (range)  
Appearance  
Total Acid Number (range)

#### Typical Property

0.840 kg/l  
4.90 to 5.40  
Bright & Clear  
13.5 to 14.5 mgKOH/g

This information only applies to products manufactured in the following location(s): South Africa

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:	Code:
08/2003	08/2006			1	

# Valvoline®