

Product Information

A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.



Valvoline Special Moly EP Grease

Description

Valvoline Special Moly EP Grease as the name indicates, is an extreme pressure grease fortified with a fine molybdenum disulphide to render a superior grease for automotive and industrial lubrication. Recommended for use as a multi purpose grease for CV joints, ball joints, steering linkage, chassis fittings, universal joints, track rollers and wheel bearings. Can be employed at operating temperatures up to 170°C. For use in trucks, tractors, draglines, bulldozers, cranes and many other off-road and industrial applications.



Advantages

- Lithium 12-Hydroxystearate Plus Molybdenum Disulphid which coats moving parts and continues to lubricate even after Grease has worked out.
- Designed for heavily loaded surfaces operating under fretting or oscillating motion.
- Excellent chemical, mechanical and storage stability.
- Protects against rust, corrosion and oxidation.
- Resists water wash-out.
- Prevents wear.

Properties

Test	Typical Property
NLGI Grade	2
Soap Type Worked Penetration @25°C 0,1mm	265/295
Drop Point °C	185
Timken OK Load Kg	21
Colour	Grey
Type	Smooth
Application temperature	-20°C to 170°C
Soap Type	Lithium



SUITABLE FOR C.V. JOINTS

This information only applies to products manufactured in the following location(s): South Africa

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:	Code:
10/1997	10/2003			1	

Valvoline®