

Product Information

A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.



Valvoline SynPower 4T

306/03

Description

Valvoline SynPower 4T is a high performance fully synthetic motor oil for all 4-cycle motorcycle engines. The product is wet clutch compatible and is recommended for Japanese and other motorcycles where API SG or JASO MA fluids are specified. This product is specially formulated to exceed the requirements of all leading engine manufacturers and provides superior protection in severe operating conditions. Valvoline SynPower 4T gives a quick cold start and smooth lubrication, even under very cold weather conditions.



Approvals / Performance Levels

API SG
JASO MA

Properties

Test	Typical Property
SAE	10W40
Viscosity, mm ² /s @ 100 °C	14.7
Viscosity, mm ² /s @ 40 °C	91
Viscosity Index	169
Viscosity, mPa.s -25 °C	<7000
Sulphated Ash, wt. %	0.82
TAN; mg KOH/g (ASTM D-664)	2.50
TBN; mg KOH/g (ASTM D-2896)	6.20
Pour Point °C	-42
Specific Gravity @ 15/15°C	0.851
Flash Point, C.O.C. °C	230

This information only applies to products manufactured in the following location(s): Europe

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:	Code:
Jan 20, 2004	N/A	306/02	AdG	1	

Valvoline®